

SURVEYOR

Model NO.	S-080600M
Camera	
Image Sensor	1/1.8" progressive scan CMOS
Main processor	S2E66
Resolution	6MP
Effective Pixels	3096(H)*2080(V)
Compression	H.264/JPEG/AVI
TV System	PAL/NTSC
Electronic Shutter Time	Auto: PAL 1/25-1/10000Sec; NTSC 1/25-1/10000Sec
S/N Ratio	≥52dB
Audio	2-way audio
Alarm	1channel Input/Output
SD Card	support 128G Micro SD
Video Output	Network/CVBS
Lens	
Focus Length	Board Lens 1.6mm/F2.0 Horizontal viewing angle: 180 °
Focus Control	Fixed
Lens Type	Fixed
Pixels	6MP
Night Vision	
Infrared LED	42μx 3PCS
Infrared Distance	20M
IR Status	Under 10 Lux By CDS
IR Power On	CDS Auto Control
Network	
Ethernet	RJ-45 (10/100Base-T)
Protocol	TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP,RTCP,NTP,SMTP
ONVIF	Support ONVIF 2.4
P2P	YES, Support QR Code
POE	internal, Support IEEE 802.3af
WIFI	N/A
Video Delay	0.3S (Within the Lan)
Stream	Mode 1:Fisheye+panorama+3*PTZ,15fps@(1280x1280),15fps@(2048x1536),15fps@(1024x768)*3 Mode 2:Fisheye or 4*PTZ,30fps@(3072x2048),30fps@(1024x768) Mode 3:Panorama main stream+Panorama sub stream,30fps@(2048x1536),30fps@(704x576)
Max Resolution	3072 × 2048
IE Brower	IE8-11, Google Chrome, Firefox, Safari, Mac Safari
Smart Phone	iPhone, iPad, Android, Android Pad
Camera Features	
Day/Night	Color/ B&W (IR-CUT)
Image Config	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, BLC, FLK(Flicker Control)
Privacy Masking	3 Rectangular Zone
WDR	Support
Recording Mode	NVR/NAS/CMS/Web
General	
Housing	Body: Metal , Bracket: Plastic
IR Cut Filter	YES
Operation Temperature	-20°C ~ +60°C RH95% Max
Power Source	DC12V±10%, 1.3A
Dimension	∅ 120 x 49(H) mm
Weight	500g